

**SCHEMA TECNICA N°158**

SCIK ACRIL ECO

Semi-gloss water-repellent acrylic paint for exposed concrete
Semi-gloss water-repellent acrylic paint for exposed concrete

DESCRIPTION

SCIK ACRIL ECO is a paint based on acrylic resins, inorganic pigments, lamellar fillers and additives.

The product has been formulated and designed for the protection of concrete structures, exposed concrete and concrete.

Thanks to its composition, SCIK ACRIL ECO has good elasticity, breathability, consolidation, uniformity of appearance.

APPLICATION

New Walls:

- The surface to be treated must be dry.
- Remove any surface granules or efflorescences by brushing or by washing.
- Proceed applying 2 coats of SCIK ACRIL ECO with brush or roller, which has to be thinned up with water in the following percentages: approx. 15-20%.

Old walls:

- The surface to be treated must be dry.
- Scrape off any loose flaking and poorly adhering coating, scraping and washing the surface with plenty of water or using a pressure washer.
- Proceed following the instruction of 'NEW WALLS' from the third point onwards.



COLORIFICIO RIVEDIL di COSIMO CODARDO

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com

TECHNICAL DATA

Nature of the bond	Acrylic copolymer in water dispersion
Viscosity	
Drying Time	2 h at touch, 6-12 h complete.
Thinning	Water 15-20%
Yield	6-8m ² /Lt
Specific weight	1,250Kg/Lt
Colors	Rivedil Color system
Dry aspect	semi-gloss
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water
Packing	13LT,5LT

CHARACTERISTICS

Characteristics:	Linea restauro.
Can be applied on:	Walls,Wood.
for:	Interiors ed Exteriors.
Certifications:	

TOOLS AND RELATED PRODUCTS

Tools:	Roller,Brush,Sprayer.
Related products:	.

SAFETY INSTRUCTIONS

The product does not require any labelling under the Decree 285 of 16/7/98 and subsequent amendments and updates. Use the product in accordance with the relevant health and safety regulations of the country. Do not dispose of the containers in the environment after use; let the residues dry and treat them as special waste. For further information please refer to **SSR158** safety data sheet.

ITEM SPECIFICATION

Semi-gloss water-repellent acrylic paint for exposed concrete. Applications to be made on the already prepared surfaces of water repellent acrylic paint SCIK ACRIL ECO based on copolymers in aqueous dispersion and mineral fillers, at least into 2 layers, in quantities determined by the support absorption. Supply and installation of material € per sqm.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

**COLORIFICIO RIVEDIL di COSIMO CODARDO**

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

PIVA 01122590753

www.rivedil.com - export@rivedil.com