



SCHEMA TECNICA N°9

SCIK TRASPIRANTE

Breathable water-based anti-condensation, anti-mould and bactericide water paint for interior finishes.

DESCRIPTION

SCIK TRASPIRANTE listed among Rivedil SUPER PAINTS, is an acrylic paint for interiors, breathable, washable and anti-mold, designed to restore walls from the most difficult agents such as mold and salt, with full respect of the environment.

SCIK TRASPIRANTE releases a pleasant almond smell during application.

Due to raw materials which give good resistance to alkali, abrasion and dirt retention, this product has also an outstanding and durable white color point, used not only for light colors but also for the dark ones, thanks to the 'Neutral' colour availability.

The final result gives a matt and uniform appearance to the support even when applied on different absorption surfaces.

Furthermore, this excellent product with a very long quality history (over 40 years) is requested by the most demanding professionals.

APPLICATION

New Walls:

- The surface to be treated must be dry. Conditions and thickness of the plaster layer affect the drying and hardening time, so make sure it has at least 28 days of curing time, depending on temperature.
- The substrate has to be well prepared and suitable for coating: dry plaster, not any granules from plaster.
- Level out imperfections of the internal support with RASAN STUCCO (check technical data sheet 48) or with K-STUKK (check technical data sheet 48a); use instead RIVENDUIT CALCE for the external support (check technical data sheet 48b). In case of holes or micro-cracks, fill the inner walls with STUCCO TRE STELLE (check technical data sheet n° 33) and the external ones with ESTERN STUCCO (check technical data sheet n° 76).
- Use the sandpaper in order to remove surface irregularities and then eliminate dust deposits.
- Treat the surface with SCIK BONIFIK (check technical data sheet n° 146) in case of mold.
- Make sure the surface is dry and apply 1 coat of SCIK PURAL ACRIL insulation (check technical data sheet n°118) or FISSATIVO ACRILICO TRE STELLE (check technical data sheet n°51), or anti-mould fixative SCIK ACRIL BONIFIK.
- Proceed applying two coats of SCIK TRASPIRANTE with brush, roller or spray, which has to be thinned up with water in the following percentages: 1st coat: approx.20-25% ; 2nd coat: approx. 15-20%. Make sure the first coat is completely dry before applying the second layer of paint.

ATTENTION: For the Neutral base, please request the data sheet that belongs to that paint, as there are different indications from the white base.

Old Walls:

- The surface to be treated must be dry.



COLORIFICIO RIVEDIL di COSIMO CODARDO

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com

TECHNICAL DATA

Nature of the bond	Vinyl copolymer paint in aqueous dispersion
Viscosity	40000 cps \pm a 10% a 30°C (viscosimetro rotazionale Brookfield)
Drying Time	1/2 h at touch, 6-12 h complete.
Thinning	20-25% 1°mano Water; 15-20% 2°mano Water
Yield	10-12m ² /Lt
Specific weight	1,657Kg/Lt
Colors	White, Neutral or colored upon request
Dry aspect	Velvety-matt
Wet aspect	Dense liquid, White
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	μ Gr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water
Packing	5LT,13LT,15LT

CHARACTERISTICS

Characteristics:	Breathable,Washable,Water repellent,battericida.
Can be applied on:	Walls,Wood.
for:	Interiors ed Exteriors.
Certifications:	

TOOLS AND RELATED PRODUCTS

Tools:	Roller,Brush,Sprayer.
Related products:	.

SAFETY INSTRUCTIONS:

Use the product in accordance with the relevant health and safety regulations of the country. Do not dispose of the containers in the environment after use; let the residues dry and treat them as special waste. For further information please refer to **SSR9** safety data sheet.

ITEM SPECIFICATION:

Breathable, washable, anti-mold acrylic paint for interiors. SCIK TRASPIRANTE cod.SKT01,based on copolymers in aqueous dispersion and mineral fillers for internal and external. Applications to be made on already prepared surfaces, at least into 2 layers, determined in quantities by the substrate absorption. Supply and installation of material € per sqm.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

**COLORIFICIO RIVEDIL di COSIMO CODARDO**

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

PIVA 01122590753

www.rivedil.com - export@rivedil.com