

**SCHEDA TECNICA N°26**

PITTURA PER CAMINETTI

Water-based fireplace paint

DESCRIPTION

PITTURA PER CAMINETTI is an acrylic paint, with an excellent filling and smoothing power.

Its formulation based on special resins in water emulsion makes this product especially recommended for the treatment and decoration of indoor and outdoor fireplaces.

APPLICATION

- The substrate has to be well prepared and suitable for coating: dry plaster, not any granules from plaster. In case of old paint make sure there is no poor or dusty paint: remove it if necessary as well as flaking paint.
- In case of holes or micro-cracks, fill with ESTERN STUCCO.
- Use the sandpaper in order to remove plaster and surface irregularities and then eliminate dust deposits.
- Proceed applying with brush, 2 coats of PITTURA PER CAMINETTI, ready to use or diluted with water as needed.



COLORIFICIO RIVEDIL di COSIMO CODARDO

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com

TECHNICAL DATA

Nature of the bond	Acrylic copolymer in water dispersion
Viscosity	
Drying Time	2 h at touch, 6-12 h complete.
Thinning	Water 5-10%
Yield	4-5m ² /Lt
Specific weight	1,500Kg/Lt
Colors	Brick red
Dry aspect	Matt
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water
Packing	0,500LT

CHARACTERISTICS

Characteristics:	Quarzo.
Can be applied on:	Walls,Wood.
for:	Interno ed Esterno.
Certifications:	

TOOLS AND RELATED PRODUCTS

Tools:	Roller,Brush.
Related products:	ESTERN STUCCO.

SAFETY INSTRUCTIONS:

The product does not require any labelling under the Decree 285 of 16/7/98 and subsequent amendments and updates. Use the product in accordance with the relevant health and safety regulations of the country. Do not dispose of the containers in the environment after use; let the residues dry and treat them as special waste. For further information please refer to **SSR26** safety data sheet.

ITEM SPECIFICATION:

Acrylic fireplace paint. Applications to be made on already prepared surfaces of acrylic fireplace paint. PITTURA PER CAMINETTI cod.PC01 based on copolymers in aqueous emulsion and mineral fillers, at least into 2 layers, determined in quantities by the substrate absorption. Supply and installation of material € per sqm.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

**COLORIFICIO RIVEDIL di COSIMO CODARDO**

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

PIVA 01122590753

www.rivedil.com - export@rivedil.com