

TEGOL QUARZ

Water-based paint for tiles

DESCRIPTION

TEGOL QUARTZ is a quartz acrylic paint, with an excellent filling and smoothing power.

Its formulation based on special resins in water emulsion makes this product especially recommended for the treatment of outdoor tiles, since it also has an exceptional resistance to atmospheric agents and pollutants.

TEGOL QUARZ is available in three different colors: tile, oxide red, dark brown.

APPLICATION


- The surface to be treated must be dry.
- The substrate has to be well prepared and suitable for coating: dry plaster, not any granules from plaster. In case of old paint make sure there is no poor or dusty paint: remove it if necessary as well as flaking paint.
- In case of holes or micro-cracks, fill with ESTERN STUCCO.
- Use the sandpaper in order to remove plaster and surface irregularities and then eliminate dust deposits.
- Apply 1 coat of SCIK PURAL ACRIL insulation or FISSATIVO ACRILICO TRE STELLE.
- Proceed applying two coats of TEGOL QUARZ with brush or roller, which has to be thinned up with water in the following percentages: 1st coat: approx.25-30% ; 2nd coat: approx. 20-25%.

Old Walls:

-The surface to be treated must be dry.

-Scrape off any loose flaking and poorly adhering coating, scraping and washing the surface with plenty of water or using a pressure washer.

-Proceed following the instruction of 'NEW WALLS' from the third point onwards.

TECHNICAL DATA	
Nature of the bond	Acrylic copolymer in aqueous emulsion
Viscosity	
Drying Time	2 h at touch, 6-12 h complete.
Thinning	Water 25-30% 1°mani 20-25% 2°mano
Yield	4-5m ² /Lt
Specific weight	1,400Kg/Lt
Colors	Tile, oxide red, dark brown.
Dry aspect	Coloured
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water
Packing	0,750LT,2,5LT,4LT,14LT
CHARACTERISICS	
Characteristics:	Quarzo.
Can be applied on:	Walls,Wood.
for:	Esterno.
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	Roller,Brush,Sprayer.
Related products:	ESTERN STUCCO,SCIK PURAL ACRIL,FISSATIVO TRE STELLE.

SAFETY INSTRUCTIONS

The product does not require any labelling under the Decree 285 of 16/7/98 and subsequent amendments and updates. Use the product in accordance with the relevant health and safety regulations of the country. Do not dispose of the containers in the environment after use; let the residues dry and treat them as special waste. For further information please refer to **SSR31** safety data sheet.

ITEM SPECIFICATION:

Quartz acrylic paint for tiles.

Applications to be made on already prepared surfaces of quartz acrylic paint. TEGOL QUARZ cod.TQ01 based on mineral fillers and copolymers in aqueous emulsion, at least into 2 layers, determined in quantities by the substrate absorption. Supply and installation of material € per sqm.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.