

**SCHEDA TECNICA N°41**

ANTIFER Z

Antirust, zinc phosphate based used for galvanized sheet

DESCRIPTION

ANTIFER Z is an anti-rust primer based on synthetic resins and zinc phosphate, used for galvanized sheet both outside and inside.

Highly anti-corrosive product, due to the antioxidant action exerted by the pigments of which it is composed.

ANTIFER Z is suitable for marine, heavy industrial environments or generally, for environments with adverse weather conditions.

APPLICATION Galvanized, aluminum and light alloy surfaces: Brush the surface, in order to remove any oxides traces. Remove any layers of old and flaky paint and sand the entire surface. Degrease the support with DILUENTE NITRO, if necessary. Proceed applying with brush or roller 2 coats of anti-rust ANTIFER Z, which has to be thinned up with ACQUA RAGIA or DILUENTE SINTETICO in the following percentages: 1st and 2nd coat: approx. 10-15%

TECHNICAL DATA	
Nature of the bond	Synthetic resins and zinc phosphates
Viscosity	
Drying Time	2 h at touch, 12-24 h complete.
Thinning	Water Ragia diluente sintetico 10-15%
Yield	8-10m ² /Lt
Specific weight	1,714Kg/Lt
Colors	Yellow, white, grey
Dry aspect	matt
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water ragia
Packing	14LT,2,5LT,0,500LT

CHARACTERISTICS	
Characteristics:	Linea antiruggini.
Can be applied on:	.
for:	Interiors ed Exteriors.
Certifications:	

TOOLS AND RELATED PRODUCTS	
Tools:	Brush,Sprayer.
Related products:	DILUENTE NITRO,AQUA RAGIA,DILUENTE SINTETICO.

SAFETY INSTRUCTIONS:

Flammable product.Keep away from heat, sparks and open flames – No smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.If swallowed, do NOT induce vomiting: immediately consult the doctor showing the product label or the container. Keep out of reach of children. Avoid release to the environment, as toxic. Do not empty into drains or the aquatic environment. For further information, please consult the SSR41 safety data sheet.

ITEM SPECIFICATION:

Antirust, zinc phosphate based used for galvanized sheet. Applications to be made on already prepared surfaces of antirust for galvanized sheet ANTIFER Z cod.AZ01 based on zinc phosphate, in at least 2 layers, in the quantities determined by the substrate absorption. Supply and installation of material € per sqm.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

**COLORIFICIO RIVEDIL di COSIMO CODARDO**

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

PIVA 01122590753

www.rivedil.com - export@rivedil.com