

RAPID RILUX

Fast drying enamel for indoor and outdoor

DESCRIPTION

RAPID RILUX is a fast drying, indoor and outdoor enamel, with a glossy effect.

Due to formulation based on modified alkyd resins, the product gives an excellent coverage and perfect resistance to atmospheric agents.

RAPID RILUX can be applied on internal and external metallic supports, suitably prepared, as industrial, agricultural and construction machinery,...

APPLICATION

INDICATIONS OF USE

NEVER PAINTED IRON METAL SURFACES:

- Remove, brushing or by washing, any flakes of foil not perfectly anchored and any traces of rust.
- Degreasing, if necessary, the support with DILUENTE NITRO.
- Make sure that the support is perfectly dry; Dust the surface and apply 2 coats of anti-rust ANTIFER R.
- After 12-24 hours, spray the application of 2 hands of RAPID RILUX, to be diluted with DILUENTE SINTETICO or DILUENTE NITRO in the following percentages: 1st and 2nd hand 10-20% approx.

PRE-PAINTED FERROUS, METAL SURFACES:

- Remove, brushing or by washing, any flakes of foil not perfectly anchored and any traces of rust.
- Remove any old paints or parts that are not perfectly adherent.
- Make sure that the support is perfectly dry; Dust the surface and apply 2 coats of anti-rust ANTIFER R.
- After 12-24 hours, spray the application of 2 hands of RAPID RILUX, to be diluted with DILUENTE SINTETICO or DILUENTE NITRO in the following percentages: 1st and 2nd hand 10-20% approx.

TECHNICAL DATA	
Nature of the bond	Alkyd Resins
Viscosity	
Drying Time	2 h at touch, 4-6 h complete.
Thinning	Diluyente sintetico o nitro 10-20%
Yield	10-12m ² /Lt
Specific weight	1,200Kg/Lt
Colors	See RAPID RILUX Color Chart
Dry aspect	Glossy
Wet aspect	
Storing	Max Temp. °C
Stability	+30@+5 years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Diluyente sintetico
Packing	14LT,2,5LT,0,750LT
CHARACTERISICS	
Characteristics:	Linea smalti.
Can be applied on:	Walls,Wood.
for:	Interiors ed Exteriors.
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	Brush,Sprayer.
Related products:	DILUENTE NITRO,ANTIFER R,DILUENTE NITRO,DILUENTE SINTETICO.

SAFETY INSTRUCTIONS

Flammable. Keep out of flames and sparks; Do not smoke; Avoid any contact with the skin and eyes; Do not inhale gases, fumes, vapors, aerosols; In case of ingestion, do not provoke vomiting; Consult your doctor immediately and show him the container or the label; Keep away from children's reach; Do not dispose of debris in drains. For more information see the SSR49 Safety Data sheet.

ITEM OF SPECIFICATIONS

Glossy fast drying enamel for outdoor and indoor.

Applications, on already predisposed surfaces, of bright enamel RAPID RILUX cod. RR01 based on modified alkyl resins, in at least 2 layers, in the quantities determined by the absorption of the support.

Supply and installation of the material €..... to the Mq.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.