

**SCHEDA TECNICA N°64**

SINT PISTA

Solvent-based synthetic paint for concrete floors.

DESCRIPTION

SINT PISTA is a low thickness solvent based synthetic paint for indoor and outdoor concrete floors. Thanks to its special formulation is SINT PISTA particularly resistant, breathable and permeable to vapour, moreover it does not retain dirt and dries quickly. It is completely washable and retains this property over time.

If SINT PISTA has to be applied on new cement substrates, the substrate must be hardened for at least 6 months, as this time allows the cement to complete the release of alkali, typical of cement.

APPLICATION

Make sure that the substrate is dry.

Remove any old paint or peeling parts that do not adhere perfectly to the wall.

In case of very absorbent or dusty substrate, apply a coat of "PRIMER CONSOLIDANTE" solvent fixative.

For the application of SINT PISTA proceed with roller or spray gun. For one-coat applications, dilute with DILUENTE SINTETICO 5-10%. For two-coat application: dilute with DILUENTE SINTETICO in the following percentages: 20-25% first coat, 5-10% second coat. Make sure that between one coat and the other the product is perfectly dried.

WARNING: Apply the product on a perfectly dry substrate and there must be no humidity in the environment. In particular, before applying the second coat, make sure that the first coat is perfectly dry (minimum 24 hours) and that there is absolutely no humidity in the environment.

TECHNICAL DATA	
Nature of the bond	Special resins.
Viscosity	
Drying Time	2 h at touch, 12-24 h complete.
Thinning	Diluyente sintetico 20-25%
Yield	4-5m ² /Lt
Specific weight	N/A
Colors	Cement grey, brick red, green and white
Dry aspect	Washable, glossy
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Diluyente sintetico
Packing	14LT,5LT

CHARACTERISTICS	
Characteristics:	Linea Speciale.
Can be applied on:	.
for:	Interno ed Esterno.
Certifications:	

TOOLS AND RELATED PRODUCTS	
Tools:	Roller,Brush.
Related products:	DILUENTE SINTETICO.

SAFETY INSTRUCTIONS

Flammable; store away from flames and sparks; do not smoke; harmful; avoid contact with skin and eyes; do not inhale gases, fumes and vapours. If swallowed, do not induce vomiting; seek medical advice immediately and show this package or label; keep out of reach of children; toxic to the environment; do not empty into drains or into water. Read SSR64 Safety Data Sheet for further information.

SPECIFICATION ITEM

Solvent-based synthetic paint for concrete floors . Applications, on already prepared surfaces, of solvent based synthetic paint SINT PISTA cod.SP01 solvent-based resins, in at least 2 layers, with a consumption determined according to the absorption of the substrate. Cost of Supply and installation of the material per sqm.:

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.



COLORIFICIO RIVEDIL di COSIMO CODARDO

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com