

SCHEDA TECNICA N°72

DILUENTE SINTETICO INODORE

Paint thinner, enamels and rust

DESCRIPTION

DILUENTE SINTETICO INODORE is a colorless liquid based on hydrocarbons mixed with high-quality isomers.

The product has been studied for the dilution of paints, varnish, enamels and rust compatible with the same.

A perfect mixing favors the application with a subsequent best anchorage to the support.

APPLICATION

- Mix DILUENTE SINTETICO INODORE in the quantities required by the technical sheets of the product to which it is intended.

TECHNICAL DATA	
Nature of the bond	Aliphatic hydrocarbon
Viscosity	
Drying Time	h complete.
Thinning	Ready to use
Yield	m ² /Lt
Specific weight	0,780Kg/Lt
Colors	
Dry aspect	Colorless
Wet aspect	Colorless liquid
Storing	Max Temp. +30°C, Min T. +5°C
Stability	years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	
Packing	20LT,5LT,1LT,0,500LT
CHARACTERISICS	
Characteristics:	Linea Diluenti.
Can be applied on:	.
for:	Interiors ed Exteriors.
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	.
Related products:	.

Flammable. Keep out of flames and sparks; Do not smoke; Harmful Avoid any contact with the skin and eyes; Do not inhale gases, fumes, vapours, aerosolos; In case of ingestion, do not provoke vomiting; Consult your doctor immediately and show him the container or the label; Keep away from children's reach; Toxic to the environment; Do not dispose of residues in sewers or in aquatic environments. For further information see the Safety Data sheet SSR71/B.

ITEM OF SPECIFICATIONS

Synthetic diluent for paints, enamels and Antiruggini.

Applications, on already predisposed surfaces, of DILUENTE SINTETICO INODORE cod. DS01 based on aliphatic hydrocarbons in the quantities required and determined by the product to which it is intended.

Supply and installation of the material €..... to the Mq.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.



COLORIFICIO RIVEDIL di COSIMO CODARDO

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com