

## VINALEGNO

### DESCRIPTION

VINALEGNO is a super concentrated vinyl glue, particularly used to weld wood materials and to glue paper. It does not stain and not turn yellowish.

### APPLICATION

- The surface to be treated must be dry and then proceed applying by brush VINALEGNO glue, ready to use.

TECHNICAL DATA	
Nature of the bond	N/A
Viscosity	
Drying Time	2 h at touch, 8-12 h complete.
Thinning	Ready to use
Yield	secondo supportom <sup>2</sup> /Lt
Specific weight	N/A
Colors	
Dry aspect	
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	µGr/m <sup>3</sup>
TVOC	N/A
PH	N/A
Cleaning	Water
Packing	5LT,0,750LT
CHARACTERISICS	
Characteristics:	Linea Isolanti.
Can be applied on:	Walls,Wood.
for:	Interno ed Esterno.
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	Roller.
Related products:	.

### SAFETY INSTRUCTIONS

The product does not require labelling under the Decree 285 of 16/7/98 and subsequent amendments and updates. Use the product in accordance with the relevant health and safety regulations of the country. Do not dispose of the containers in the environment after use; let the residues dry and treat them as special waste. For further information please refer to **SSR79** safety data sheet.

### ITEM SPECIFICATION

Vynil glue for wood and paper.

Applications of vynil glue, to be made on already prepared surfaces. VINALEGNO cod.VL02 suitable for welding wood supports or paper, determined in quantities by the substrate absorption.

Supply and installation of material € ..... per sqm.

### NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.