

**SCHEMA TECNICA N°93**

ANTIFER R

Fast-drying anti-rust treatment for iron

DESCRIPTION

ANTIFER R is a fast-drying anti-rust primer based on alkyd and phenolic resins, used for ferrous metal surfaces.

Due to its formulation based on special pigments, the product, is endowed with high anticorrosive power.

ANTIFER R is easy to apply and provides also good expansion, excellent elasticity and adhesion to the surface.

ANTIFER R is available in red, grey and black color.

APPLICATION

New ferrous metal surfaces :

- Brush the surface, in order to remove any leaf flakes and ensure that any rust traces are cleaned up.
- Dust the surface and make sure the support is dry.
- Degrease the support with DILUENTE NITRO, if necessary.
- Proceed applying with brush or spray, 2 coats of anti-rust ANTIFER R, which has to be thinned up with DILUENTE SINTETICO in the following percentages: 1st and 2nd coat approx. 10-20%.

Pre-painted ferrous metal surfaces:

- Remove any layers of old and flaky paint or imperfectly anchored parts. Manually remove the rust.
- Roughen the support for a better anchorage.
- Proceed as for the 'New ferrous metal surfaces' from the fourth point onwards.

TECHNICAL DATA	
Nature of the bond	Alkyd and phenolic resins
Viscosity	
Drying Time	2 h at touch, 12-24 h complete.
Thinning	Diluyente sintetico diluente nitro 20-25%
Yield	8-10m ² /Lt
Specific weight	1,714Kg/Lt
Colors	Red, Grey, Black
Dry aspect	Colored
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Diluente nitro
Packing	14LT,2,5LT,0,500LT

CHARACTERISTICS	
Characteristics:	Linea antiruggini.
Can be applied on:	.
for:	Interiors ed Exteriors.
Certifications:	

TOOLS AND RELATED PRODUCTS	
Tools:	Brush,Sprayer.
Related products:	DILUENTE NITRO,DILUENTE SINTETICO.

SAFETY INSTRUCTIONS:

Flammable product. Keep away from heat, sparks and open flames – No smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.If swallowed, do NOT induce vomiting: immediately consult the doctor showing the product label or the container. Keep out of reach of children. Avoid release to the environment, as toxic. Do not empty into drains or the aquatic environment. For further information, please consult the SSR93 safety data sheet.

ITEM SPECIFICATION:

Fast-drying anti-rust treatment for iron. Applications to be made on already prepared surfaces of anti-rust treatment for iron ANTIFER R cod. AR01 based on modified alkyd resins, in at least 2 layers, in the quantities determined by the absorption of the support. Supply and installation of the material €..... to the sqm.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.



COLORIFICIO RIVEDIL di COSIMO CODARDO

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com