

MURAL 2 TIPO A

Water-based siloxane water-repellent

DESCRIPTION

MURAL 2 TIPO A is a wall protection product, based on non-filmogenic siloxane resins, designed as a specific treatment for the protection of pietra leccese (Lecce stone), both inside and outside.

MURAL 2 TIPO A creates a water-repellent barrier, penetrating deeply into the substrate and leaving the water vapor permeability unchanged. Therefore the walls will always be perfectly dry: no water penetrates inside while water vapor comes out.

In addition, besides protecting the support, MURAL 2 TIPO A does not affect the color and the aspect.

APPLICATION

Pietra leccese (Lecce stone) surfaces:

- Brush the surface, in order to remove any loose laces and ensure that surface crusts and traces of dirt are cleaned up.
- In the presence of molds, treat the surface with SCIK BONIFIK.
- Make sure the surface is dry and with a brush, roller or spray proceed applying 1 coat of MURAL 2 TIPO A ready to use.

NB: It is absolutely necessary to apply the product from the bottom upwards, for the best aesthetic and qualitative result.

We also advise to protect the floors and to ensure the complete evaporation of the product before staying in the treated environment.

TECHNICAL DATA

Nature of the bond	Non-filmogenic siloxane resins
Viscosity	
Drying Time	2 h at touch, 12-24 h complete.
Thinning	Ready to use
Yield	4-5m ² /Lt
Specific weight	N/A
Colors	transparent
Dry aspect	transparent
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water
Packing	15LT,5LT,0,750LT

CHARACTERISICS

Characteristics:	Linea idrorepellenti.
Can be applied on:	Walls,Wood.
for:	Interiors ed Exteriors.
Certifications:	

TOOLS AND RELATED PRODUCTS

Tools:	Brush,Sprayer.
Related products:	SCIK BONIFIK.

SAFETY INSTRUCTIONS

The product does not require labelling under the Decree 285 of 16/7/98 and subsequent amendments and updates. Use the product in accordance with the relevant health and safety regulations of the country. Do not dispose of the containers in the environment after use; let the residues dry and treat them as special waste. For further information please refer to **SSR142** safety data sheet.

ITEM SPECIFICATION:

Protective, water based siloxane water-repellent for internal and external surfaces. Applications to be made on already prepared surfaces of water based siloxane water-repellent MURAL 2 TIPO A cod.M2T01 based on non-filmogenic siloxane resins, in a single layer, in the quantities determined by the substrate absorption. Supply and installation of material € per sqm.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

colorificio
Rivedil
made in Italy

COLORIFICIO RIVEDIL di COSIMO CODARDO
Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy
Tel. (+39) 0832 731293 - (+39) 0832 731273
P.IVA 01122590753
www.rivedil.com - export@rivedil.com