

SCHEDA TECNICA N°172

ACQUARIA IMPREGNATE COLORATA

Water finish for coloured wood

DESCRIPTION

ACQUARIA IMPREGNANTE COLORATA is a colored water-based finish for wood for interiors and exteriors. The product is suitable for the treatment of all wooden articles requiring excellent resistance to atmospheric agents, ultra violet rays and does not alter the appearance and grain of the wood on which it is applied.

ACQUARIA IMPREGNANTE COLORATA is easily applied with excellent dilatation that allows you to follow the appearance and grain of the wood without leafing maintains a uniform color. It also has a rapid drying as well as having a very low environmental impact.

APPLICATION

New Wood:

- Sand to remove any raised wood flakes.
- Clean the surface and check that the wood is not damp. grouting imperfections with PASTA STUCCO. Sand the grouting and remove the dust.
- After 6-12 hours, brush or spray the application of 2 coats of ACQUARIA IMPREGNANTE COLORATA, ready to use (or with a 5% max of water). Mix the product thoroughly before use. Pass between the two hands of about 4-6 hours
- Avoid application in case of annealing less than 5 °c and above 30 °c, do not apply in case of relative humidity always higher than 85% and under direct sunlight or in case of probable rain.

Already varnished wood:

- Check the condition of the old paints. Remove the peeling parts or not perfectly adherent and clean carefully.
- Proceed as for the new wood surfaces from the second point onwards.



COLORIFICIO RIVEDIL di COSIMO CODARDO

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy Tel. (+39) 0832 731293 - (+39) 0832 731273 P.IVA 01122590753

www.rivedil.com - export@rivedil.com

TECHNICAL DATA	
Nature of the bond	Resin in aqueous dispersion
Viscosity	
Drying Time	h complete.
Thinning	
Yield	m²/Lt
Specific weight	N/A
Colors	See Linea Legno chart
Dry aspect	Colorful
Wet aspect	Colorful
Storing	Max Temp. °C
Stability	years (in sealed, unopened original packing)
voc	$\mu Gr/m^3$
TVOC	N/A
PH	N/A
Cleaning	
Packing	
CHARACTERISTICS	
Characteristics:	
Can be applied on:	Wood.
for:	
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	
Related products:	

SAFETY INSTRUCTIONS

Use the product according to the current hygiene and safety regulations; after use do not disperse the package in the environment; leave the residues to dry well and treat them as special waste. For further information read SSR172 Safety Data Sheet.

SPECIFICATION ITEM

Water-based colored finish for wood, outdoor and indoor use. Applications, on already prepared surfaces, of ACQUARIA IMPREGNATE COLORATA cod. AIC, based on resins in water dispersion and mineral fillers, in at least 2 coats, in the quantities determined by the absorption of the substrate. Cost of the supply and application of the material in sq.m...

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions. The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge, however, being elements such as weather conditions, labor, tools, quality of third party products and others, not under the direct control of the Rivedil, this document does not constitute a warranty, nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document. We recommend that you always check the suitability of the product to each specific instance. This supersedes all previous editions.



COLORIFICIO RIVEDIL di COSIMO CODARDO

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy Tel. (+39) 0832 731293 - (+39) 0832 731273 P.IVA 01122590753

www.rivedil.com - export@rivedil.com