

SCHEDA TECNICA N°173

ACQUARIA VERNICE TRASPARENTE BRILLANTE

Transparent water finish for wood

DESCRIPTION

ACQUARIA VERNICE TRASPARENTE BRILLANTE is a transparent finish to water for indoor and outdoor wood. The product is suitable for the treatment of all wood products that require an excellent resistance to atmospheric agents, ultra violet rays and does not alter the appearance and grain of the wood on which it is applied.

ACQUARIA VERNICE TRASPARENTE BRILLANTE does not yellowing and is easily applied with excellent dilatation that allows you to follow the appearance and grain of the wood without browsing. It also has a rapid drying as well as having a very low environmental impact.

APPLICATION

New Wood:

- Sand to remove any raised wood flakes.
- Clean the surface and check that the wood is not damp.
- grouting imperfections with PASTA STUCCO. Sand the grouting and remove the dust.
- After 6-12 hours, brush or spray the application of 2 coats of ACQUARIA VERNICE TRASPARENTE BRILLANTE, ready to use (or with a 5% max of water). Mix the product thoroughly before use. Pass between the two hands of about 4-6 hours
- Avoid application in case of annealing less than 5 °c and above 30 °c, do not apply in case of relative humidity always higher than 85% and under direct sunlight or in case of probable rain.

Wood already painted:

- Check the condition of the old paints. Remove the peeling parts or not perfectly adherent and clean carefully.
- Proceed as for the new wood surfaces from the second point onwards.

TECHNICAL DATA	
Nature of the bond	Resin in aqueous dispersion
Viscosity	
Drying Time	h complete.
Thinning	
Yield	m ² /Lt
Specific weight	N/A
Colors	Transparent
Dry aspect	Colorless
Wet aspect	Colorless
Storing	Max Temp. °C
Stability	years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	
Packing	
CHARACTERISICS	
Characteristics:	.
Can be applied on:	Wood.
for:	.
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	.
Related products:	.

Safety Instructions

Use the product according to the current hygiene and safety standards; Do not disperse containers in the environment after use; Let the residues dry well and treat them as special waste.

For more information see the SSR173 Safety Data sheet.

Item of specifications

Water finishing for transparent wood for exteriors and interiors.

Applications, on already pre-disposed surfaces, of ACQUARIA VERNICE TRASPARENTE BRILLANTE cod. AVTB based on resins in aqueous dispersion and mineral fillers, in at least 2 layers, in the quantities determined by the absorption of the support.

Supply and installation of the material €..... to the Mq.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.

- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.

- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.