

SCHEDA TECNICA N°208

T.D'ITALIA INCANTO COLORED FLAKE

Decorative finish made of colored flocculi

DESCRIPTION

TERRE D'ITALIA SERIE INCANTO is the new decorative cycle based on natural oxides that recalls the beauty and the nuances of the beautiful colors of the Italian peninsula.

TERRE D'ITALIA SERIE INCANTO is simple and quick to apply, yet is an elegant and refined decoration with pearlescent effects, having excellent washability characteristics, suitable for every type of environment, both classic and modern.

The system has 8 bases with 8 different colors of flocculi, with a choice of 7 pearlescent pastes (INCANTO ORO, INCANTO VERDE, INCANTO VIOLA, INCANTO ROSSO, INCANTO BLU, INCANTO ARANCIO, INCANTO ARGENTO):

YELLOW FLOCCULO: TD Puglia RED FLOCCULO: TD Sicilia ORANGE FLOCCULO: TD Umbria BLU FLOCCULO: TD Sardegna GREEN FLOCCULO: TD Abruzzo GREY FLOCCULO: TD Trentino BROWN FLOCCULO: TD Toscana WHITE FLOCCULO: TD NEUTRO

APPLICATION

- Make sure the surface is completely dry . If the surface is plastered, make sure it had a curing time of at least 28 days , depending on temperature.
- Make sure that the media has been well prepared and is suitable for coating: plaster must be dry, not have any granules, on old walls, make sure that there is no poor quality or powdery paint, remove flaking paint etc.
- Apply 1 coat of SCIK PURAL ACRIL primer if necessary.
- Apply with a brush or roller one or two coats of DECOR FONDO COLORED PRIMER diluted with 5-10 % water.
- Apply TERRE D'ITALIA SERIE INCANTO, ready to use and mixed with the chosed pearlescent INCANTO paste, using the special SPALTER brush. FINISH COLORATION:
- TERRE D'ITALIA SERIE INCANTO It.0,750 + INCANTO pearlescent paste 0,190 kg / 0,150 Lt. TERRE D'ITALIA SERIE INCANTO Lt.2,5 + INCANTO pearlescent paste 0,600 kg / 0,500 Lt. We recommend using an average amount of product and apply the product in a criss-cross pattern so to evenly distribute the flocculi.
- After roughly 10-20 minutes, whilst not yet completely dry, fade the product using the SPATOLA TD tool.

TECHNICAL DATA	
Nature of the bond	special resins in aqueous solution
Viscosity	
Drying Time	2 h at touch, 6-12 h complete.
Thinning	Ready to use
Yield	6-7m²/Lt
Specific weight	1,025Kg/Lt
Colors	Yellow,Red,Orange,Blue,Green,Grey,White
Dry aspect	Pearlescent Terre with colored flocculi
Wet aspect	Liquid with the presence of colored flocculi
Storing	Max Temp. +30°C, Min T. +5°C
Stability	10-12 Months (in sealed, unopened original packing)
voc	30μGr/m³
TVOC	130μGr/m³
РН	7-8°C
Cleaning	Water and Soap
Packing	0.750LT,2.5LT
CHARACTERISTICS	
Characteristics:	Washable, Environmentally friendly.
Can be applied on:	Walls, Wood.
for:	Interiors.
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	Spalter 100,Spalter 70,TD Spalter.
Related products:	DECOR FONDO (COLORATO),INCANTO (ADDITIVO).

CAUTION:

- The flocculi in the product are obtained by chemical reaction, for this reason: we can not guarantee the same characteristics from one floculi to another; stability is also limited in time. It is therefore recommended to use the same lot for the same work to be carried out. If this is not possible, manually mix the batches together (do not use an electromechanical tool).

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions. The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge, however, being elements such as weather conditions, labor, tools, quality of third party products and others, not under the direct control of the Rivedil, this document does not constitute a warranty, nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document. We recommend that you always check the suitability of the product to each specific instance. This supersedes all previous editions.