

PATINE CALCE

Antique effect decorative paint

DESCRIPTION

PATINE CALCE is a special decorative paint for interiors and exteriors, based on lime and special additives which confers to the product its special antique effect.

One of the main features of this product is its extreme easy of use and delicate look, which make it the ideal choice for all kinds of environments and styles.

PATINE CALCE combines breathability and washable features together.

The washability of the product can be even further increased applying CERA D'ARTE once completed the application process, available in NEUTRAL, for a semi-glossy effect: GOLD, SILVER, GREEN, PURPLE, BLUE and RED for a pearlescent semi-glossy effect, or applying HYDRO FINISH OPACO, for a matt inaltered effect, or even HYDROFINISH SPECIALE, if you wish to apply PATINE CALCE outdoors.

APPLICATION

- Make sure the surface is completely dry . If the surface is plastered, make sure it had a curing time of at least 28 days , depending on temperature.
- Make sure that the media has been well prepared and is suitable for coating: plaster must be dry, not have any granules , on old walls, make sure that there is no poor quality or powdery paint, remove flaking paint etc..
- Apply 1 coat of SCIK PURAL ACRIL primer if necessary.
- Apply with a brush or roller one or two coats of HYDROFONDO AM diluted with 5-10 % water.
- Apply the first coat of PATINE CALCE, previously colored using the BASE COLOR U.P.C. toners, using the PLAFONE special tool. Use alternate strokes, applying a minimal amount of product. Wait until perfectly dry, then lay the second coat of PATINE CALCE with circular movements, pressing with the PLAFONE tool to obtain the tipical shaded effects.

DECORAZIONI RIVEDIL S.r.l.

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 03937370751

www.rivedil.com - export@rivedil.com

TECHNICAL DATA	
Nature of the bond	Special mixtrure of resins in lime
Viscosity	
Drying Time	2 h at touch, 6-12 h complete.
Thinning	Ready to use
Yield	10-14m ² /Lt
Specific weight	N/A
Colors	Neutral,to be colored,see chart
Dry aspect	Matt antique effect veil
Wet aspect	Yellowish liquid
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	150µGr/m ³
TVOC	40µGr/m ³
PH	11-12°C
Cleaning	Water and Soap
Packing	0.750LT,4LT
CHARACTERISICS	
Characterisics:	Washable,Traspirabile.
Can be applied on:	Walls,Wood.
for:	Interiors/Exteriors.
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	3x10cm Brush,7x17cm Brush,3x7cm Brush.
Related products:	.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

DECORAZIONI RIVEDIL S.r.l.

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 03937370751

www.rivedil.com - export@rivedil.com