

TRAVERTINO

Decorative coating travertine marble effect

DESCRIPTION

TRAVERTINO is a new top quality italian natural lime based decorative product.

TRAVERTINO is in powder form and is to be mixed with water.

Its ease of application allows you to achieve the effect of modern and classical Italian marble and travertine stones.

TRAVERTINO is available in two grain sizes: Fine and Coarse.

APPLICATION

- 1) Make sure the surface is completely dry . If the surface is plastered, make sure it had a curing time of at least 28 days , depending on temperature.
- 2) Make sure that the media has been well prepared and is suitable for coating: plaster must be dry, not have any granules , on old walls, make sure that there is no poor quality or powdery paint, remove flaking paint etc. .
- 3) Apply 1 coat of SCIK PURAL ACRIL primer if necessary.
- 4) Apply with a brush or roller one or two coats of DECOR FONDO PRIMER diluted with 5-10 % water.
- 5) Mix TRAVERTINO POWDER with 30-35 % of water, in order to create a homogeneous paste workable with a steel trowel.
- 6) Apply evenly to the first coat of stucco (white, not colored) with a stainless steel trowel . Allow to dry completely. Continue with the desired effect ...

DAMASCATO effect: Points 1-6 as indicated above, hence:

- Apply the second coat with the same tool and dab with a stainless steel trowel .
- Prior to complete drying smooth with steel trowel . Allow to dry completely .
- Apply Sahara (Silver or Gold) with glitter using a sponge according to personal taste .

STRIPED EFFECT Points 1-6 as indicated above, hence:

- Once you applied the second coat, when the area is still fresh , scratch horizontally from right to left the surface. Scratching with the cutting blade of the stainless steel trowel that you are using.
- Smooth lightly the entire surface with a trowel. During this phase the typical effect of roman marble will become evident.
- After complete drying, you can paint the surface with a finish (Sahara Gold or Silver colored with Toner TN) , or protect it with protective Hydro Finish Matte , depending on the desired effect.

BETON COLORED TRAVERTINO EFFECT Steps 1-5 as shown above, hence:

- Color TRAVERTINO with the chosen Toner TN .
- Apply evenly the first coat of stucco (previously colored with Toner TN) with a stainless steel trowel . Allow to dry completely .
- Apply the second coat with the same tool and smooth using stainless steel trowel .

BETON EFFECT WITH COLORED HYDRO FINISH Steps 1-6 as shown above :

- Apply the second coat with the same tool at the same time smooth using a stainless steel trowel .
- Once completely dry, paint the surface with Hydro Finish Matt (colored with Toner TN) to obtain the desired effect . Special Effects
- Depending on personal taste you can also simulate the shape of bricks or blocks of marble. This effect could be achieved by applying paper tape before the second coat, creating the texture of the bricks or blocks of marble. When you have finished applying the second coat, remove the tape prior to drying. You will obtain a distinguishable brick effect

DECORAZIONI RIVEDIL S.r.l.

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 03937370751

www.rivedil.com - export@rivedil.com

TECHNICAL DATA	
Nature of the bond	N/A
Viscosity	
Drying Time	12-24 h complete.
Thinning	30%-35% Water
Yield	0,8-0,9m ² /Kg for FINO; 0,6-0,7m ² /Kg for GROSSO
Specific weight	N/A
Colors	White
Dry aspect	Travertine marble effect
Wet aspect	Powder
Storing	Max Temp. °C
Stability	2 years (in sealed, unopened original packing)
VOC	10µGr/m ³
TVOC	40µGr/m ³
PH	11-12°C
Cleaning	Water and Soap
Packing	20KG
CHARACTERISICS	
Characterisics:	Breathable, Anti-mildew.
Can be applied on:	Walls, Wood.
for:	Interiors/Exteriors.
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	Stainless Steel Trowel 200x80cm, Stainless Steel Trowel 240x100cm,.
Related products:	DECOR FONDO (WHITE), SAHARA ARGENTO, SAHARA ORO, HYDRO FINISH OPACO.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

DECORAZIONI RIVEDIL S.r.l.

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 03937370751

www.rivedil.com - export@rivedil.com